

FULL TECHNICAL REPORT · STATUS AS OF NOVEMBER 15, 2026

NOVA

Crew health, handled entirely inside the ship, with NASA flight software at the core.



CHALLENGE
Create Health Monitoring Software for Astronauts on Space Missions

TEAM
Nicolás Moreno · Benjamín Campos · Nicolás Richardson · Luis González · Ambar Martínez · Daniella Mora

CORE
F Prime v4.4.2 · NASA JPL · Apache 2.0, the framework that flew the Ingenuity helicopter

Team B&N concept for the NASA International Space Apps Challenge. Not affiliated with or endorsed by NASA. Vital signs in screenshots are simulated or for demonstration.

EXECUTIVE SUMMARY

An on-board doctor that doesn't wait for Earth.

On a trip to Mars, a consult with the flight surgeon takes 6 to 44 minutes round trip, and during solar conjunction the link drops for weeks. NOVA handles monitoring, detection and first response inside the ship. Vital signs flow through a core built on F Prime; the crew sees them on the screen, on their phone and over the patient's body in augmented reality; a local assistant answers from open medical sources. Earth receives a report every night and sends back signed updates.

4 custom components in F Prime v4.4.2	5 local models: language, search, voice, hearing and vision	35,830 passages from 41 openly licensed medical sources	13 emergency protocols, each with its source
10 protocols guided over the body in augmented reality	~13 ms body vision per frame, on the ship's GPU	3.8 GB all on-board models, on disk	0 internet calls in the flight architecture

Three principles

01 · ALL ON BOARD

No critical function depends on the cloud or on Earth. Models, library, voice and vision run on the same ship computer.

02 · FIXED RULES

Thresholds live in the flight core and emergency steps come from a reviewable file. The model explains and assists; it does not decide.

03 · THE PERSON DECIDES

Each crew member chooses what to share. Mood leaves the phone only if they share their day; what they write never leaves.

What changed since the Nov 14 report

- **NOVA Station.** Shared tablet that turns personal with an NFC card or a single-use QR.
- **Radiation.** Mission dose against 600 mSv, solar storm alert and shelter protocol.
- **Constellations.** The week of whoever shares their day, with no invented data.
- **Team research.** Earth → space learning, eye vision and radiation detector.
- **Luis's physical station.** RC522 reader and live AD8232 ECG, with pulse and HRV stored as real data.
- **Mission.** Solar system, the 1,018 days and the crew on a single screen.
- **Eyes.** Eyes and fatigue measured with the camera, using Nicolás Richardson's method.
- **Bibliography and data.** Every source, dataset and license at the end of the report; public repository.

CONTENTS

Eight parts, from the ship to the bibliography

INTRODUCTION

04 The full technology stack

05 On-board AI models

I · ARCHITECTURE

06 Overview

07 The path of a data point

08 F Prime flight core

09 F Prime in detail

10 Medical station and simulator

11 Ship services

12 The link: full API

II · THE SHIP SCREEN

13 NOVA PC

14 Vitals and vital-sign forecast

15 Body twin, the anatomical twin

16 Mind, mental health

17 Constellations

18 Ask NOVA and swappable brain

19 Medical library

20 3D medical kit

21 Mission, Home and systems

22 Mission on one screen

23 Radiation and solar storms

III · EMERGENCIES AND AUGMENTED REALITY

24 Emergencies: 13 protocols

25 On-board vision

26 Body scan

27 Eyes: eyes and fatigue

28 Hologram by system

29 CPR by gravity

30 Procedures on the body

31 Control from the station

IV · NOVA STATION AND HARDWARE

32 The shared tablet

33 Tablet sheets and link

34 Station architecture

35 The assembled station

36 Exploded view

37 Part by part: structure

38 Part by part: electronics

39 Live ECG

V · PHONE AND EARTH

40 Mobile app in mission mode

41 Emergency, Home and scan on the phone

42 Women's health and exercise

43 Earth console

44 Signed ship ↔ Earth loop

VI · TEAM RESEARCH

45 Earth → space learning

46 Eye health and radiation detector

VII · RIGOR AND STATUS

47 NASA material and open sources

48 Licenses and credits

49 Clinical safety and privacy

50 How we verified it

51 Status by component

52 Open items, risks and plan

53 Annex: running it all and glossary

VIII · BIBLIOGRAPHY AND DATA

54 Data and its origin

55 NASA documents

56 Open library

57 Papers and technical references

Team B&N

Nicolás Moreno
Software engineer · product design. Builds NOVA PC, the core and the app.

Benjamín Campos
Physics engineer · data science and agentic models. Earth → space learning.

Nicolás Richardson
Physics engineer · data science and computer vision. Eye vision.

Luis González
Physics engineer · hardware and robotics. Physical station and radiation detector.

Ambar Martínez
Clinical and educational psychologist · neuropsychology. Wellbeing and private session.

Daniella Mora
PhD candidate in Physics (UC) · particle physics, with experience at CERN.

Everything that runs on the ship, by layer

Open software end to end, chosen to run offline on a single computer. Each piece has its license verified (page 48). Versions are those installed today.

Flight core
Vitals, rules, alerts and commands

- **F Prime 4.4.2** — NASA JPL · flight framework
- **C++** — 4 custom components
- **CMake** — fprime-util build
- **Python 3.12** — F Prime GDS

Link and desktop
The ship screen and API

- **Rust 1.99** — Link, services, signatures
- **Tauri 2** — Native window
- **axum 0.8 · tokio** — HTTP, SSE and WebSocket
- **rustls · rcgen** — Own HTTPS :8751
- **ed25519-dalek 2** — Signed packages

On-board AI
Language, search, voice, hearing, vision

- **llama.cpp b12110** — Qwen3 4B · nomic embed
- **whisper.cpp** — large-v3-turbo
- **ONNX Runtime** — Kokoro-82M voice
- **MediaPipe 1.2.3** — Pose heavy + Hands, GPU
- **Hugging Face** — Source of the weights

Interface and 3D
What the crew sees

- **JavaScript** — ES modules, no framework
- **three.js** — Twin, kit and hologram
- **WebGL** — Custom shaders
- **pdf.js 5.4.296** — Library reader
- **WebAssembly** — Scanned JPEG 2000

Phone
Each crew member, their app

- **Expo 57** — Builds and OTA
- **React Native 0.86** — React 19.2
- **Android** — “Home” widget

Tools
Data, tests and environment

- **Node.js 24** — Scripts and tests
- **Puppeteer** — End-to-end tests
- **uv** — Python environments
- **Git · GitHub** — Private repository

Hardware
Today and in flight

- **Apple M5 Pro** — Development, Metal GPU
- **Jetson class** — Flight target · next
- **Medical station** — USB serial or UDP · Luis

≈ 14,000	38	7	0
own lines on the ship (Rust, C++, JS, Python), not counting the app	commits in the ship repository since November 5	local services the ship starts and watches on its own	cloud services in the flight architecture


Logos from Simple Icons (CC0) and icons from Lucide (ISC); trademarks belong to their owners. F Prime: logo of the NASA JPL open project (Apache 2.0).

Five models that fit in the ship's computer

Each model runs in its own service, only on `127.0.0.1`; the ship starts and watches it. If one is missing, it carries on without it and says so. Memory measured with everything running, on Nov 14.

FUNCTION	MODEL	ENGINE · PORT	DISK	LICENSE
Language	Qwen3-4B-Instruct-2507 · Q4_K_M · 16,384 context, 2 parallel turns, prefix cache	llama.cpp b12110 · Metal · `:8081`	2.50 GB	Apache 2.0
Search	nomic-embed-text-v2-moe · Q4_K_M · 768 dimensions, multilingual	llama.cpp `--embedding` · `:8084`	344 MB	Apache 2.0
Hearing	Whisper large-v3-turbo · q5_0 · automatic language	whisper.cpp · `:8083`	574 MB	MIT
Voice	Kokoro-82M v1.0 · voice af_heart (English), ef_dora (Spanish)	ONNX Runtime · Python 3.12 · `:8082`	337 MB	Apache 2.0
Vision	MediaPipe Pose Landmarker heavy (3D points and mask) + Hand Landmarker	MediaPipe 1.2.3 · GPU · `:8792` behind `/v1/vision/ws`	38.5 MB	Apache 2.0

MEMORY IN USE, MEASURED



Resident memory of each process. Total near 4.1 GB: fits in an 8 GB flight computer with margin.

FAST WHERE IT MATTERS

Rules and protocols go first in the prompt: with the prefix cache NOVA starts answering in about 1.5 s. Vision takes about 13 ms per frame.

WHAT THE MODELS DON'T DO


They do not decide medical steps or thresholds. Emergencies answer with fixed text: the model once denied a reported arrest because the sensor did not show it.

OPTIONAL DEMO, DECLARED

For the demo the brain can be Claude; the screen says "demo brain · Claude" and falls back to the on-board model on its own. It stays outside the flight architecture.


Everything lives inside the ship

The dotted turquoise border is the hull: everything inside works without Earth. The only thing that crosses is a slow link, with light delay, that sends a report down and signed packages up.



From the station to the screen in under a second

A real case from the demo: the simulator applies the “fainting” scenario and Ingrid's pulse drops to 34 beats per minute. This is how that value passes through each piece, top to bottom in time.




- **Reading · 1 Hz.** One message per measurement with crew member, sensor, value, unit and quality from 0 to 1. Max 1 KB.
- **Classification.** Plausible range per sensor; quality below 0.5 does not alert. Raising the level is immediate; lowering it takes 10 s in a row.
- **Silence · 120 s.** If a sensor that has reported goes quiet, the core emits `SIN_DATOS`.
- **Status · 1 Hz.** 4 crew members × 18 sensors with value, level and age; each alert goes out instantly.
- **Screens.** NOVA PC gets the continuous stream; phones read `/v1/estado` every 5 s.
- **Earth.** The report goes down with light delay; commands go up through a queue with a computed arrival time.

< 1 s	10 s	120 s	9.9 min
from sensor to screen	in a row to lower the level	of silence and the core warns	to Earth, today (day 220)

F Prime, the software that flew Ingenuity

F Prime is JPL's flight software framework, open under the Apache 2.0 license. NOVA includes it as a submodule in `vuelo/lib/fprime` and adds its own deployment, `Nova/Nave`: the standard subsystems plus four custom components, joined by typed ports.



COMPONENT	WHAT IT DOES	INPUTS AND OUTPUTS
Estacion	Reads the medical station each cycle without blocking and drops invalid JSON with the event `MENSAJE_INVALIDO`.	`UDP 50050` to `Nova.Signo`
MonitorSalud	Classifies each reading against the attention threshold and the Earth notice threshold. Warns if a sensor is silent 120 s.	31 parameters in `prmDb` · `WARNING_HI/LO`
Pantalla	Publishes the full crew status at 1 Hz and each alert instantly.	`UDP 50051 · 50052`
Salud	Shared types: sensors, levels and the vital sign as a struct.	FPP

RATE

1 Hz to read and classify; 0.5 and 0.25 Hz for resources and the health of the system itself.

FROM EARTH

Thresholds change by dictionary command, are stored in `prmDb` and survive a restart.


SYSTEMS VIEW

fprime-gds with the NOVA interface: events, telemetry and commands decoded with the deployment dictionaries.

v4.4.2	31	3	Apache 2.0
F Prime, as a submodule	flight parameters by command	rate groups: 1, 0.5 and 0.25 Hz	open license from JPL

Two thresholds per side and a rule against false alarms

The health monitor compares each reading with two limits: **attention**, handled by the crew, and **Earth notice**, which calls the flight surgeon. The 31 limits are F Prime parameters: they live in `prmDb`, change by command and the screen draws them exactly as they are in the core.



LEVEL UP: IMMEDIATE

DOWN: 10 S IN A ROW AT THE LOWER LEVEL

INDICATOR	PHYSICAL RANGE	ATTENTION	EARTH NOTICE	BASIS OF THE STARTING VALUE
Pulse bpm	20–250	≥110 · ≤45	≥140 · ≤35	tachycardia >100, bradycardia <50
SpO₂ %	50–100	≤94	≤90	hypoxemia below 90%
Systolic mmHg	50–250	≥140 · ≤90	≥180 · ≤80	ACC/AHA 2017; hypotension <90
Diastolic mmHg	30–150	≥90	≥120	ACC/AHA 2017
Temperature °C	30–43	≥38.0 · ≤35.5	≥39.5 · ≤35.0	fever ≥38; hypothermia <35
Breathing rpm	4–60	≥24 · ≤10	≥30 · ≤8	clinical early warning
Glucose mg/dL	20–600	≤70 · ≥180	≤54 · ≥250	ADA: level 1 and 2 hypoglycemia
Cabin CO_2 ppm	0–10,000	≥2,600	≥5,000	NASA-STD-3001 vol. 2
Sleep h	0–16	≤5.9	≤3.5	cautious rule: under 6 h
Mood · energy 1–5	1–5	≤2	never	only if the person shares their day

Starting values (`docs/umbrales.md`), all "pending" until a physician validates them. HRV, resting pulse, steps, light, noise, cabin O_2 and temperature have no fixed threshold: they will be compared with each person's baseline.

ESTACION

Passive component at 1 Hz. Reads up to 256 messages per cycle without blocking, checks unit and range, and raises `PERDIDA` if the station is silent 15 s.

MONITORSALUD

Active component with a queue. A reading with quality below 0.5 is stored without alerting; an impossible value is dropped as a sensor error, not an emergency.

PANTALLA

Bridge to NOVA PC: sends the full status and each alert over UDP 50051 and receives what the crew enters by hand on 50052.

4
health events: ALERTA_TIERRA, ALERTA_ATENCION, VUELVE_NORMAL, SIN_DATOS

0.5
minimum quality to alert

120 s
without data, then warns (parameter)

10
max warnings per impossible value

A data contract to connect any hardware

The medical station talks to the core through an open contract: one JSON line per measurement (NDJSON). If the message meets the contract, the core understands it without knowing which board is behind it. Luis's station, the simulator and the phones come in through the same door.

TRANSPORT

UDP to port 50050, one message per datagram, max 1 KB, UTF-8 ending in a newline. The contract also proposes USB serial at 115,200 baud to avoid depending on the network; the `Estacion` component reads only UDP today. Phones come in through `/v1/lote`.

{} ONE MEASUREMENT


```
{"v":1,"tipo":"medicion","est":"estacion-1",
"t":1763164800123,"trip":"T2","sensor":"spo
2",
"valor":97,"unidad":"%","calidad":0.92}
```


The unit is checked against the contract table; if it does not match, the message is dropped with its reason.

TYPE	PURPOSE	WHAT THE CORE DOES TODAY
medicion	vital signs, cabin and the 7 phone sensors	in use validates and classifies
latido	the station is still alive, every 5 s	in use 15 s without signal = `PERDIDA`
onda	numbered ECG or PPG chunks	partial sign of life
evento	`sin_contacto`, `movimiento`, `error_sensor`...	partial sign of life

The simulator: real variability and five scenarios

Until the physical station is present, `estacion/simulador/simulador.py` sends messages with the same contract. Pulse, SpO_2 and breathing follow, second by second, the variability of four records from the BIDMC PPG and Respiration Dataset (PhysioNet, ODC-By 1.0), one per crew member, on top of their baseline. It sends pulse and SpO_2 every 1 s, breathing every 2 s, HRV and temperature every 10 s, pressure every 15 s and glucose every 30 s. Scenarios are requested in the terminal or over UDP 50053.


SCENARIO	WHAT CHANGES	TIMING
desmayo T3	pulse −26 (Ingrid at 34 bpm), pressure −48/−34	drops in 20 s, recovers at 3 min
hipoglucemia T1	glucose −46 mg/dL, pulse +38, HRV −25 ms	120 s ramp
fiebre T2	temperature +2.0 °C, pulse +22, breathing +5	150 s ramp
hipoxia T4	SpO_2 −11%, pulse +30, breathing +10	60 s ramp
co2 · normal	cabin CO_2 +1,500 ppm · all to baseline	immediate

`sembrar_diarios.py` leaves two weeks of sleep, mood and energy for the Mind view. Luis's physical station already reads ECG and cards (pages 34 to 39); with `NOVA_SIN_SIMULADOR=1` the ship does not start the simulator.

A single program starts and watches everything else

NOVA PC (Tauri, with its link in Rust) is the only thing to open. Once it starts, with or without a window, it brings up the seven on-board services, checks them every 3 seconds and restarts any that crashes. What is already running is not duplicated and each service writes its log to `~/.nova-pc/logs/`.

SERVICE	PORT	PROGRAM	LOG
Flight core	TCP 5080	`fprime-gds`: starts `Nova_Nave` and serves the Systems API	`nucleo.log`
Language	TCP 8081	`llama-server`: Qwen3 4B Q4_K_M, 16k context, on GPU	`modelo.log`
Voice	TCP 8082	`voz/servidor.py` with Kokoro-82M	`voz.log`
Hearing	TCP 8083	`whisper-server`: large-v3-turbo q5_0	`oido.log`
Search	TCP 8084	`llama-server --embedding`: nomic-embed v2	`busqueda.log`
Vision	TCP 8792	`vision/servidor.py`: MediaPipe Pose and Hands	`vision.log`
Simulator	UDP 50053	`simulador.py` (not with `NOVA_SIN_SIMULADOR=1`)	`simulador.log`



The link: two doors and a single API

HTTP :8750

Screens, phones and Earth console. Serves the interface and the API; every response carries `no-cache`, so the screen always loads the new version.

HTTPS :8751

The same app with its own certificate (rcgen + rustls), since the browser grants the camera only to secure pages. It includes today's IPs and is rebuilt if they change.

OPTIONAL TOKEN

With `NOVA_TOKEN`, the 8 routes that write from outside (phones, viewers, Earth, Home) require the header `x-nova-token`.

VARIABLE	WHAT IT CHANGES
`--sin-ventana`	link only: another monitor, an analog or tests
`NOVA_SIN_SERVICIOS=1`	each piece is started by hand (annex)
`NOVA_PUERTO_ENLACE`	a test ship on another port
`NOVA_MODELO` · `_OIDO` · `_VOZ` …	a service on another computer

Thirty-nine routes for screens, phones, viewers and Earth

All come from `tripulacion/src-tauri/src/main.rs` and answer the same on :8750 and :8751. GET reads, POST writes, WS is WebSocket. Those marked with 🔑 require `x-nova-token` when the ship sets `NOVA_TOKEN`.

LIVE STATUS		
GET	/v1/flujo	status and alerts (SSE)
GET	/v1/estado	latest full status
GET	/v1/mision	day and light delay
GET	/v1/salud	link version
WHAT ENTERS THE CORE		
POST	/v1/lote 🔑	phone readings
POST	/v1/ingreso	manual measurement
POST	/v1/escenario	demo: scenario
HISTORY		
GET	/v1/historia	series for one sign
GET	/v1/resumen	24 h: mean, min, max
ASK NOVA		
POST	/v1/preguntar	live answer (SSE)
GET	/v1/modelo	active brain
POST	/v1/opinion	was the answer useful?
POST	/v1/oir	speech to text
POST	/v1/decir	text to speech
MEDICAL LIBRARY		
GET	/v1/biblioteca	the 41 sources
GET	/v1/biblioteca/buscar	passages by meaning
POST	/v1/biblioteca/recargar	reload the index
GET	/v1/biblioteca/pdf/…	original PDF
MEDICAL KIT		
GET	/v1/kit	inventory
POST	/v1/kit/buscar	query the graph
POST	/v1/kit/uso	log a use
POST	/v1/kit/ajuste	correct a count

EMERGENCIES AND PRIVACY		
G·P	/v1/bitacora	on-board log
POST	/v1/privado 🔑	surgeon only
SCAN AND VISION		
POST	/v1/escaner/cuadro 🔑	frame; orders return
GET	/v1/escaner/flujo	latest frame (SSE)
GET	/v1/escaner/visores	who's scanning
POST	/v1/escaner/orden 🔑	drive a viewer
WS	/v1/vision/ws	bridge to vision
HOME		
GET	/v1/casa	inbox
GET	/v1/casa/archivo/{id}	attachment
POST	/v1/casa/respuesta	reply
POST	/v1/casa/subida 🔑	arrives from Earth
POST	/v1/casa/bajada 🔑	goes down to Earth
SYSTEMS AND EARTH		
GET	/v1/sistemas	F Prime events
POST	/v1/sistemas/comando 🔑	delayed command
GET	/v1/tierra/informe	nightly report
GET	/v1/tierra/estado	the ship, delayed
POST	/v1/tierra/actualizar 🔑	signed package
GET	/v1/aprende	what arrived
INTERFACE		
GET	/ · /escaner.html	interface

39	8	3	6 MB
/v1 routes plus the original PDFs	protected by token	SSE streams: status, scan, NOVA	limit per request

A screen for the crew, readable from two meters

NOVA PC is the ship's desktop window (Tauri) and the same interface served by the link on `:8750`. It receives the F Prime core status once per second over SSE and shows it in eight views. The **Crew** view is the home view: the four crew members side by side, with NOVA on the right.



Crew view, Nov 14, 2026, mission day 220. Pulse ring, rhythm and six vital signs per crew member. Kenji shows in amber for a mood of 2/5 in his check-in.

⚠ NOVA CARDS

Each warning comes from fixed rules, not the model: what changed, what to do and the source. Low pulse and pressure together open the fainting guide. **Acknowledge** mutes it 2 min if the level does not rise.

⛶ FILLS ANY WINDOW

Designed for 1800×1000, `escala.js` scales it by a factor of 0.68 to 1.35: text grows with the window and the grid shares out the rest. Works on a laptop or on the module screen.


ON-BOARD VOICE AND HEARING

Speaks with Kokoro sentence by sentence; if it fails, it uses the system voice, also offline. Listens with whisper.cpp: cuts after 0.9 s of silence and does not hear itself.

VIEW	WHAT IT SHOWS	STATUS
Crew · Vitals · Body twin · Mind	Live · history and forecast (14) · 3D twin (15) · mental state (16)	in use
Live body scan	The AR scan seen from the ship, with remote control of the viewer (part III)	in use
Medical kit · Systems · Library	3D rack (20) · F Prime core (21) · library and reader (19)	in use

Each sign's history and what comes in the next 15 minutes

The Vitals view draws the history stored on board (1 Hz for 6 h and per minute for 30 days, on disk; windows of 10 min to 7 days) with the core's current thresholds on top, projects each sign forward and warns when something departs from what is expected.



Kenji's pulse, last hour. In lilac, the 15 min cone: 55 ±18 bpm, with a 14% chance of landing at the attention threshold (≤ 45).

- **Trend.** Weighted least squares over that person's last 30 min, with more weight on recent data (15 min constant).
- **Cone.** Projects a quarter of the chosen window, up to 15 min. Width is ±2 deviations and grows with the horizon.
- **Crossing probability.** The chance of passing the attention threshold at the end of the horizon. Above 30% the cone turns amber.
- **Unexpected change.** If the latest reading lands more than 3 deviations from what the trend expected, the panel marks it as *unexpected change*.

ⓘ HONEST SCOPE


Simple, explainable statistics on each person's data, in the spirit of world models: predict and act on the prediction. It is neither a learned model nor clinically validated. It runs only with readings from the last 30 s.

Each vital sign, read through the spaceflight hazard that drives it

HAZARD (NASA HRP)	WHAT NOVA WATCHES	HOW
Space radiation	Cumulative mission dose	MSL RAD rates: 1.84 mSv/day in cruise, 0.64 on Mars; limit 600 mSv
Isolation and confinement	Sleep, mood, energy, HRV	Shared check-ins and heart rate variability
Distance from Earth	Blood sugar and light delay	No resupply or evacuation
Gravity fields	Pulse and pressure	Fluids shift up and the heart adapts
Hostile, closed environment	SpO_2, breathing, temperature, CO_2	Cabin air reaches the body

A 3D anatomical twin colored with today's data

Each crew member has a reference body that can be rotated, zoomed and opened by layers. Ten regions are colored by their status: live from the F Prime core, or estimated by the on-board model with NASA-published rates, and the card says which of the two it is.



Mara's twin, day 220. Skin, skeleton and organs on; on the right, the ten regions with today's value. These are reference bodies, not a scan of the person.

REAL, OPEN ANATOMY

Male: BodyParts3D 4.0, 2,234 structures (© DBCLS, CC BY 4.0), 33 MB. **Female:** MakeHuman silhouette (CC0) with organs from NIH HuBMAP v1.5 (CC BY 4.0), 18 MB. Six layers: skin, skeleton, organs, muscles, vessels and nerves.


ONE CARD PER REGION

Heart, lungs, brain, eyes, neck veins, hip, spine, legs, kidneys and skin. What it does, what space does to it, how it is today and what to do, with its source (NASA HRP, Twins Study, Marshall-Goebel 2019).

PROJECTION	ON-BOARD RULE	RATE SOURCE
Hip bone	1.25%/month in weightlessness; completed exercise cuts it by up to half	NASA HRP: 1 to 1.5%/month without countermeasures
Leg muscle	Up to 20% on a 120-day curve; exercise removes up to 65%	NASA, muscle atrophy fact sheet
Spine	Up to +3 cm in the first days, and it stays	NASA HRP, disc injury risk
Mars gravity	0.38 g counts as 40% of a weightless day	assumed no human data yet

How the crew is doing mentally, told with care

Isolation shows first in sleep and mood. The Mind view joins two sources: each person's live signs compared with their own 24 h average, and the daily check-in each crew member chooses to share from their phone.



Kenji, day 220. The brain shows “Stressed” from a mood of 2/5 and 6.0 h of sleep. On the right, 14 days of mood for all four; below, sleep, energy and body signals against each person's usual.

SIX STATES WITH FIXED RULES

Rest, focus, stress, fatigue, calm and high arousal. Physical cases first: pulse −12 and pressure −25 against the usual (low blood to the brain), SpO_2 under 92 %, glucose under 70 or fever from 38 °C. Then a score from pulse, breathing and variability, and last the check-in: mood ≤ 2/5 or under 6 h of sleep. Each state shows its reasons in plain words.

PRIVATE BY DEFAULT

Mood, energy and sleep reach the ship only if the person shares their day; what they write in their journal never leaves the phone. NOVA names them with care and only when they matter (rule 6 of its prompt). On Earth, the flight surgeon gets summaries with consent via `/v1/privado`.

A MODEL TO EXPLAIN

The particle brain comes from OpenPsico (B&N, three.js r170, served locally) and its activity profiles are conceptual: they are not fitted to EEG or MRI. It helps the crew understand what happens in the body; it does not measure the mind.

Each crew member's week, drawn as their sky

Constellations is a new tab in Mind. It shows mood, energy and sleep for the last 7 or 14 days of those who share their day from the phone. The ship does not invent days: it reads one journal per person and, if someone does not share, their sky stays empty and says so.



Each person. Four compact constellations, the same as in each app: height is mood, each star's size is hours slept and the card compares the week with the previous one. Demo data.

TWO READINGS

Each person (default) shows each one's constellation with its palette and a dot that runs through the week. **Together** puts the whole crew on one chart, with a cursor per day, buttons to show or hide people and a table view with a fixed name column. Colors are a categorical palette validated for dark backgrounds, fixed per seat.

ONLY WHAT THE PERSON SHARES

In the app, "Share my day" sends the ship the last 14 days of check-in and sleep, each with its date. The ship stores them in a journal per person (`/v1/diario`) with the name of who wrote it. The simulator no longer invents mood, energy and sleep for real people. The card warns if the check-in was the same every day.





WHAT IT IS FOR

Mood dropping in several people at once points to something in the environment (sleep, workload, an event) more than to one person. It lets the crew and the psychologist on Earth talk with data; it classifies no one.

An assistant that answers with ship data and cites its sources

The crew asks NOVA in writing or by voice. The ship builds the answer in `/v1/preguntar`: it first decides whether it is an emergency, computes priorities with fixed rules and passes the model only what it needs. The model writes; it does not decide medical steps.





Answer with citations. The numbers open the real page in the library.

The brain can be swapped, and the screen always says which one


BRAIN	WHAT IT IS	WHEN IT IS USED	STATUS
Onboard default	Qwen3 4B Instruct 2507 (Q4_K_M) on llama.cpp, `:8081`, with prefix cache: starts answering in ~1.5 s	Always. It is the flight architecture: no internet. The screen says "onboard · no internet".	in use
Demo	Claude Opus 5.5 via the Anthropic API, low effort, with automatic fallback	Only with `NOVA_CEREBRO=claude` and the key in the environment. The screen says "demo brain · Claude"; if it does not answer, it falls back to the onboard model.	optional

Emergencies never go through the model: in a test the small model denied a cardiac arrest the crew reported because the sensor did not show it. Since then, what a person reports rules and NOVA answers with the fixed protocol text.

41 open sources and the real page of each citation, offline

Everything NOVA knows about medicine comes from documents stored on the ship, each license checked one by one. They are searched by meaning in English or Spanish and each result opens the original PDF on its page, with the passage marked.

41	35,830	768	3
sources in use, of 42	passages with source and page	dimensions, nomic-embed v2	passages per question



Search "CPR in microgravity". Passages on the left; on the right, page 5 of the DGLRM/ESAM 2020 guideline (Scand J Trauma Resusc Emerg Med, CC BY 4.0) with the passage highlighted. Out for licensing: StatPearls, WikEM, Harrison, Tintinalli, UpToDate.

HYBRID SEARCH

Meaning (vectors) plus a keyword boost. Indexes, references and repeated legal notices are not cited.

PAGE READER

Local pdf.js 5.4 (Apache 2.0), with JPEG 2000 in wasm for scans. Marks the passage on the real page.

INCREMENTAL INDEX

`indexar.py` rebuilds only what changed (sha256). The ship reloads the index without restarting.

ORIGIN	SOURCES	EXAMPLES AND LICENSE
NASA	26	HRP (13), OCHMO (10), Shuttle medical checklist, ISS kit · federal work or NTRS
Textbooks	5	Four OpenStax (CC BY-NC-SA 4.0) · Gray's Anatomy 1918 (public domain)
WHO, ICRC and MedlinePlus	5	Basic Emergency Care, essential medicines, mhGAP, Doing What Matters (CC BY-NC-SA 3.0 IGO) · MedlinePlus
Papers and trauma	5	CPR in microgravity and three on women's health (CC BY 4.0) · TCCC 2026

The medical kit as an object graph NOVA can walk through

On Mars there is no resupply. The medical kit lives on the ship as a live inventory: each supply with its quantity, drawer, expiry and the protocols that use it. NOVA reads it before naming anything, so it says where it is and how many are left.



Drawer A open, day 221. Advanced life support: the drawer slides out and releases its supplies as cards with their real photo; on the right, each supply with its quantity and expiry.

3D RACK

Six drawers in the Space Station style. They slide out on touch and release their supplies as cards with a real photo: 42 free Wikimedia Commons photos, credited.

EMERGENCY MODE

Choosing an emergency lights up only the drawers and supplies of that protocol, with a thread of light from each card to its drawer.

AUTONOMY

The day each supply runs out or expires, against day 259 (Mars) and 1,018 (return). Each use is logged in `kit.json`.

Ask the rack in plain words

SCENE GRAPH


As in ConceptGraphs (Gu et al., 2023), `/v1/kit/buscar` passes the rack to the brain as a list of objects: what it is, what it is for, where it is and how many are left.

THE SHIP VERIFIES

Only objects that exist in the rack count and the ship sets the real drawer. The screen opens it and NOVA says it out loud.

The ship knows where it is, how long light takes and when each message arrives

`mision.rs` propagates Earth and Mars with Standish's J2000 orbital elements (JPL), solves Kepler's equation and places the ship on a Hohmann transfer leaving April 8, 2026, with 500 days on Mars. That delay feeds everything that crosses to Earth.



FIELD IN /V1/MISION	TODAY
Mission day · phase	220 · cruise
Mars arrival	day 259, in 39 days
Distance to Earth	≈ 178 M km
Light delay	9.9 min each way
Solar conjunction	no · elongation 86.8°


Below 2° of elongation there is solar conjunction and commands are suspended. With `NOVA_LANZAMIENTO` and `NOVA_ESTADIA_DIAS` any mission day can be rehearsed.

HOME: FAMILY ALSO TRAVELS WITH LIGHT

Family texts and photos (`tierra/casa.py`) arrive with the light delay at the time of sending and only then appear on the phone and the “Home” widget. Replies wait for the next contact.

SYSTEMS: THE CORE IN THE CREW'S WORDS

`tierra.rs` reads the F Prime GDS (`:5080`) every second and translates it with the deployment dictionaries. A command from Earth waits out the light delay before entering the core.



Onboard systems. Core online, real-time health, medical station connected, F Prime events in plain language and the current thresholds set by the flight surgeon.

The mission and the crew on a single screen

The Mission view brings together what used to be spread out: where the ship is going, how long light takes, how much is left and how each person is. It uses the same orbital calculation from `mision.rs` (Standish J2000 elements and Hohmann transfer), now also drawn on screen.



Day 221 of 1,018, Nov 15, 2026. Solar system with the light signal traveling between the ship and Earth (10.0 min each way, 180 M km), mission figures on the right, timeline below and crew readiness with what arrives from their apps.

LIVE SOLAR SYSTEM

Earth, Mars and the ship in their real position for the day. The cursor gives distances and delay. In a solar storm the particle waves are visible.

THE 1,018 DAYS

Cruise to Mars, 500 days on Mars and return. It can be dragged to any day, back to Today or play the whole mission.

CREW READINESS


Heart, sleep, steps, HRV, mood, energy and alert. Each cell says where it comes from and how old it is; simulated data is marked. A click opens their Vitals.

FIGURES IN VIEW

Mission day and percentage, Mars arrival, light to Earth and reply time, stable crew, how much of what is measured is real, 24 h cabin CO_2 against the 5,000 ppm limit and mission radiation against the 600 mSv career limit. The screen fits whole at 1600×1000 and 1440×900, no scroll.

Radiation, with its dose, its limit and a shelter

Radiation is one of the HRP's five hazards of spaceflight and it cannot be felt. `radiacion.rs` receives the reading from the detector Luis designed (`POST /v1/radiacion`). Until that detector exists, the ship estimates the rate from Curiosity's MSL RAD measurements and says so on screen.




Radiation, day 221. Ship cutaway with a 20 g/cm² hull and a shelter with 10 cm of extra water (OCHMO, p. 10; illustrative). Current rate 79 µSv/h simulated, 408 mSv accumulated, 68 % of the career limit.

FIGURE	HOW IT IS COMPUTED	SOURCE
Rate in cruise and on Mars	≈ 1.84 mSv/day in cruise and ≈ 0.64 mSv/day on the surface, until the detector arrives	Zeitlin 2013 · Hassler 2014
Mission dose	Accumulated day by day; at this rate it crosses 600 mSv on day ~452, already on Mars, and ends at ~1,270 mSv	NASA-STD-3001 Vol. 1
Solar storm alert	Detector fast channel, or ≥ 500 µSv/h sustained for 30 s; the peak and event dose are logged	Detector design · HRP SPE
Per-event limit	Event dose compared with 250 mSv	NASA-STD-3001

PROTOCOL "TORMENTA_SOLAR"

Banner on every view, NOVA's voice and a guide for the whole crew: go to the shelter, with live radiation. Cites OCHMO Radiation Protection (p. 1, 2, 4 and 10) and the HRP report on SPE syndromes (p. 10). It is protocol 13. NOVA turns amber and restless and looks toward the Sun.



Thirteen fixed protocols, with the source in view

When someone writes or says an emergency, the ship answers with the written protocol, without going through the language model. The step-by-step guide asks, measures and decides with the crew member's real values, in English or Spanish.

13	87	7	0
protocols in `ui/protocolos.json` v0.2	branching steps in the 11 step-by-step guides	protocols with cited source and page	language model decisions in an emergency

PROTOCOL	GUIDE	SOURCE AND PAGE	EARTH NOTICE
Cardiac arrest in microgravity	10 steps	DGLRM/ESAM, CPR in microgravity · p. 2, 4–6, 8	Always, immediately
Possible fainting (syncope)	8 steps	No page cited yet	Always
Low blood sugar	6 steps	No page cited yet	Below 54 mg/dL or if it recurs
Fever	5 steps	No page cited yet	From 39.5 °C
Low oxygen saturation	7 steps	No page cited yet	Below 90 % sustained
Severe allergic reaction	9 steps	WHO, Basic Emergency Care (BEC) · p. 119, 202, 235	Always
Choking	8 steps	WHO, BEC · p. 155 · CPR guide · p. 4	In the nightly report
Severe bleeding	8 steps	WHO, Basic Emergency Care · p. 169–170	With tourniquet or if it won't stop
Seizure	8 steps	WHO, Basic Emergency Care · p. 141–142	Always
Decompression sickness	10 steps	NASA HRP, DCS and hypoxia · p. 52 · OCHMO · p. 6, 12	Always; immediately if type 2
Solar particle storm	8 steps	OCHMO, Radiation Protection · p. 1, 2, 10 · HRP SPE · p. 10	Always: the event dose when it ends
Rising cabin CO_2	List	Cabin steps	Above the notice limit
Little sleep, low mood or energy	List	Self-care steps	Never on its own: the person decides

FIXED TEXT

The ship recognizes the emergency (`nova::emergencia`) and returns the written steps and where the needed items are in the kit. What the crew reports overrides a sensor.

BRANCHING GUIDE

Question, action, wait or close. Waits read the twin against the protocol thresholds. During compressions a metronome plays at 110 per minute.


LOG

Each answer is logged with a time and the Earth console reads it at `/v1/bitacora`. The fainting guide opens on its own if pulse and pressure drop together.

Status: `demo · pending flight surgeon review`. Licenses: CC BY 4.0, CC BY-NC-SA 3.0 IGO and NASA public use.

The phone sees, the ship thinks

The scanner works like a headset tethered to a computer. The phone shows its own camera without waiting on the network and sends each frame to the ship, which runs the heavy models on its GPU and returns only the body points. If the ship does not answer, the phone does the vision with light models and says so on screen.



ONLY RESULTS RETURN: 33 POINTS IN THE IMAGE + 33 IN METERS, 96 PX MASK (1–3 KB), 21 POINTS PER HAND

FALLBACK ON THE PHONE

If the ship does not answer, the phone runs Pose lite (full on a PC) and Hands in WebAssembly, with the image at 384 px. Results come in through the same path.

TIMEWARP ON THE PHONE

Each result carries its frame's time. The points are predicted to display time (up to 60 ms) and the gyroscope subtracts how far the phone turned meanwhile.

NO QUEUE

Vision always processes the newest frame and drops old ones. An answer for frame N closes all earlier ones, and a frame with no answer in 400 ms is counted as lost. The hologram never falls behind by piling up work.

THE PATIENT FIRST

With two people in view, the patient is the one with the most horizontal torso: the one standing is the rescuer. Each phone has its own tracker (up to 4) so two cameras do not mix up the same person. The mask is cropped to the patient only.

SELF-CALIBRATING GYROSCOPE

Gyroscope axes differ between phones. NOVA learns them by comparing the measured rotation with how the body points moved, and only uses the sign when the relation is clear. It can be turned off from the station.

SECURE PAGE ON THE SHIP NETWORK


The phone's browser only gives the camera to a secure page. The ship generates its certificate with `rcgen` (localhost, nova.local and its IP), stores it in `~/.nova-pc/tls` and remakes it if the IP changes. The ship starts vision, restarts it if it crashes, and vision shuts down if the ship dies.

MediaPipe Tasks 1.2.3 on the ship · Python · websockets · OpenCV · axum · tokio-tungstenite · rustls · tasks-vision on the phone · Metal GPU

Measured Nov 14 on the development Mac: ~13 ms per frame with both models (pose 4.8 ms on GPU, hands 8.0 ms), 25–47 ms round trip shown in the headset. not measured on a real phone inside a headset


The anatomy fits the body in front of you

You point the phone at a crew member and NOVA overlays their reference anatomy, sized to that person, turned the way they stand and at their distance. The organs beat and breathe with the live values of their twin.



Live at Space Apps Santiago, Nov 15. The full skeleton fitted on a team member, arms included, with estimated bone density and the vitals strip below. Top left, what it measured: 46 cm torso at 1.3 m. Demo crew data.

- **Where it is.** Position comes from a least-squares fit of MediaPipe's 3D points against the same points in the image, with a perspective camera (67° field of view on the phone, 60° on a PC, adjustable from the station). This gives the real distance.
- **How big it is.** Shoulder width (MediaPipe × 1.18, calibrated) and torso length are averaged over the first frames. The anatomy is scaled between 0.85 and 1.35 times the reference, and length does not change if the hips leave the frame.
- **How it bends.** Three bones (pelvis, chest and head) are blended by height in the shader, like an animation skeleton. Arms and legs have one rigid bone per segment, and are drawn only if their joints are visible in the frame.
- **A window inside.** The torso outline is projected, clipped to the person's silhouette and darkened like a cavity. Hands passing in front cover the hologram.
- **Three styles.** Hologram (glowing edges, the default), clinical (shaded, solid organs) and X-ray (bright bone, faint tissue). They switch live from the station.



At the hackathon. The ship screen follows what the headset sees.

ATLAS

BodyParts3D 4.0 (male) with the liver from the Human Reference Atlas (HuBMAP), CC BY 4.0. 689 parts, 9.6 MB compressed.

RENDER

three.js with custom shaders over the camera image, at the phone's screen refresh rate.

WHAT IT IS NOT

An estimate from proportions, not an image of the inside. The start screen says so before beginning.

The eyes, measured with the camera and compared with oneself

Spaceflight-associated neuro-ocular syndrome (SANS) and tiredness show in the eyes. The scanner adds the Eyes system with Nicolás Richardson's ocular vision method: MediaPipe Face Landmarker on the same device, at full resolution, with the same model he measured (sha256 verified).



Eyes live. Opening of each eye, upper and lower eyelid to pupil, blinks per minute, distance, head stillness and alertness level. Tested on a team member at Space Apps, looking at the Eye check red dot.

MEASURES AND THEIR NOISE

Millimeters assume an 11.7 mm iris. There is a stillness gate and blinks are excluded. The 20 s "Eye check" looking at a red dot stores the median on the ship (`/v1/ojos`) and compares it with that person's and that camera's baseline. It only asks for follow-up if the change exceeds the minimal detectable change (MDC95) Richardson measured: 1.8 mm in opening, 1.2 mm in upper eyelid and 0.9 mm in lower.

TIREDNESS, NOT EMOTIONS


PERCLOS over the last minute (eyes ≥ 80 % closed; Dinges and Grace, 1998): from 7.5 % "some signs", from 15 % "tired". It adds blink duration, closures of 0.5 s or more and yawns. An Eye check with tiredness in the last 12 h shows up in Mind with its reason. NOVA knows it does not read emotions from the face.

WHAT IT DOES NOT DO


It does not diagnose SANS: it flags a change and suggests repeating the next day and reading a near-vision chart. Pupil–brow distance is not used because its MDC (3.3 mm) does not yet allow useful changes to be seen. It was measured with one camera and one person; clinical validation is pending.

Six body systems, each with its own data


In hologram style, the chosen system lights up in its color and the rest stays as a faint outline. A panel anchored to the organ shows the values and their curve over the last ten minutes, and says where each number comes from: measured, estimated or reported by the person.



Cardiovascular. The heart highlighted inside the rib cage.



Respiratory. Lungs with live SpO_2 and breaths per minute.



Skeletal. Skeleton with arms and estimated bone density (−2.1 %).

SYSTEM	WHAT LIGHTS UP	WHAT IT SHOWS	DATA ORIGIN
Cardiovascular	Heart, aorta and vena cava	Heart rate and systolic pressure	measured · live
Respiratory	Lungs	SpO_2 and breaths per minute	measured · live
Metabolic	Liver, pancreas, stomach, intestines	Glucose	continuous sensor
Renal	Kidneys	Kidney stone risk	estimated · demo
Skeletal	Skeleton, skull and 8 arm and leg segments	Bone density −2.1 %	estimated · demo
Neurological	Brain	Mood from 1 to 5 and hours of sleep	shared by the person

DRIVEN BY THE TWIN

The heart beats at the crew member's pulse and the lungs inflate at their breathing rate. It is the same live state as the rest of the ship.

COLOR BY LEVEL

An organ with an out-of-range value pulses in its level's color: lilac to watch, amber for attention and magenta for an Earth notice, the same levels as the flight core.


SWEEP ON DETECTION

When a body appears or you switch crew member, the hologram reveals itself from head to pelvis in 1.4 s. Curves are requested from `/v1/historia` every 5 s.

Renal and skeletal show fixed demo values for now: the ship does not yet receive urine tests or densitometry. The screen marks them as estimated.

No weight, no compression: the technique changes with gravity

On Earth the rescuer's weight does the work. On Mars it weighs 38 % and in cruise nothing. NOVA picks the technique by mission phase (cruise = microgravity, Mars = 0.38 g) or the one the crew sets, marks the compression point on the chest and counts compressions by watching the hands.



Microgravity CPR mode, live at the hackathon. Compression point, 100–120 per minute and 5–6 cm, the Evetts-Russomano technique with its source and the reaction arrow for anchoring.

GRAVITY	TECHNIQUE NOVA GUIDES
Earth · 1 g	Standard: straight arms, weight does the work (ERC/AHA)
Mars · 0.38 g	Straddling, pushing with arms and shoulders; swap often (Sriharan 2021; Overbeek, Life 2022)
0 g · rec. 2	Evetts-Russomano on the spot, no straps
0 g · rec. 2	Reverse bear hug, from behind, if the previous one fails
0 g · rec. 3	Handstand with the patient on the restraint system (CMRS): the strongest
0 g · rec. 4–5	Patient and rescuer restrained; the guideline reserves defibrillation for this case

Microgravity: DGLRM/ESAM guideline for CPR in spaceflight, Hinkelbein et al., Scand J Trauma Resusc Emerg Med 2020 (CC BY 4.0) and AWMF 2022; the recommendation number appears on screen next to each technique.

COUNTING COMPRESSIONS

Only hands within a quarter of the body size from the CPR point are used. Their vertical motion, normalized by body size, marks each compression. The rate is the median of the intervals over the last 5 s. A compression is good if the rate is between 100 and 120, and its depth between 5 and 6 cm when the camera sees from the side.

WHEN TO SWITCH RESCUERS

NOVA compares four plans over a 3-minute horizon (switch now, in 40 s, at 2:00 or keep going) and suggests the one that loses the fewest quality minutes. It assumes exponential fatigue that sets in sooner in microgravity (140 s) than on Mars (170 s) or Earth (240 s), counts 5 s hands-off per switch and moves it up if the rate drops below 100.

THE FLOATING PATIENT

In microgravity a push moves the patient away. NOVA measures how far the body drifts in one second (compressions go back and forth and cancel out), subtracts the phone's rotation and, above 12 cm/s, draws its path and asks to hold the patient before compressing.

A VOICE THAT CORRECTS LITTLE

NOVA speaks when something changes: the technique for this gravity, a patient drifting away or a rate out of range (“Faster. Aim for 100 to 120 a minute.”). It leaves at least 4 s between sentences. The first counter was tuned with a real CPR video: it counted 8 of 11 compressions with no false positives.

assumed The fatigue constants are design assumptions and do not come from a study. Depth is only estimated from the side. It still needs testing with a manikin and a rescuer.

36 steps shown on the patient's body

The steps of the emergency guides can be followed with the body scan. For each step NOVA knows where it goes (a point on the fitted body), what to watch (the rescuer's hands, a timer, the twin's vitals) and when to speak. The text comes from the protocol; AR only places it.

not tested with a rescuer



PROTOCOL	STEPS	WHAT IS SHOWN ON THE BODY
Cardiac arrest	5	CPR mode with the technique for the gravity; AED pads below the right collarbone and on the left side
Fainting	5	Shoulder to call them, chest to check breathing, cuff 2 cm above the elbow crease
Low blood sugar	4	15 g of fast sugar next to the mouth, the kit drawer and live glucose
Fever	2	Thermometer in the ear or on the forehead, live temperature and pulse
Low oxygen	2	Finger sensor placed well; breathe in 4 s and out 6 s
Anaphylaxis	6	Epinephrine 0.5 mg intramuscular in the outer thigh (drawer A); the second dose, in the other thigh
Choking	3	Fist above the navel with an arrow inward and upward; 5 blows between the shoulder blades
Bleeding	3	The wound you mark with a tap; the tourniquet higher on the same limb, never over a joint
Seizure	4	Clear space around the head and a seizure timer
Decompression	2	Joints where to ask about pain or tingling

An instructor who speaks little · rules from the HoloAssist study (Wang et al., 2023)

CONFIRM AND CORRECT

With the hands 1.2 s on the point, NOVA says "Good. That is the spot.". If they are close but off, it corrects with a body reference and the distance ("No. 4 centimeters toward the head"): after 0.8 s on a critical step and after 3 s on one that is not.

FOLLOW WITHOUT NAGGING

If the hands stay still for 4 s away from the point or the step takes 1.5 times the expected time, NOVA redirects. It speaks at most one sentence every 3 s and never repeats the same one within 8 s.

WAITS DECIDE WITH THE TWIN

When a wait ends, NOVA reads the crew member's values against the protocol's own recovery thresholds, picks the branch and says why ("Recovered: Glucose 96").

EVERYTHING IS WRITTEN DOWN


Each intervention is logged as instruct, confirm, correct, follow, decide or close, with who started it, and reaches the station live.

With the phone in the headset, the PC runs everything

Inside the headset nobody can touch the phone. So every scanner setting is also a button in the **Live body scan** view of NOVA Station, which also shows what the headset sees.



"Control the viewer" panel. What is lit is the state the phone reports, not the last click.



- **No new connection.** The command rides in the response to the frame the phone already sends to the station, about 0.1 s after the click. The phone's own buttons go through the same function.
- **The step, in both eyes.** In the headset the procedure card sat in one eye only, with buttons nobody could touch. Now the step is drawn inside the image and says "answer on NOVA Station".
- **The wound, with one click.** In a hemorrhage, the wound is marked by clicking on the live image; the point reaches the phone as a coordinate of its own frame.



The headset at Space Apps. The phone sits inside the headset; the step is drawn in both eyes and the PC runs everything.

LIVE BODY SCAN	HOW
Live image	960 px JPEG, up to ~12 per second
One headset at a time	Released after 3 s without frames
Join	QR code to the secure link


`15 / 15` End-to-end test on November 14 with a simulated phone in headset mode: every control changed the phone and the panel reflected it, with no page errors. `untested` Marking the wound from the PC (needs a real body in front of the camera) and a physical headset.

One tablet for everyone that turns personal with a card

NOVA Station is the fixed sick-bay tablet, standing at 30° on Luis's station. Without a card it shows shared content and the emergency; with a crew member's NFC card or QR it opens their space. It is an Expo app in kiosk mode that loads `station.html` from the ship and records the microphone so NOVA can listen (`/v1/oir`).



Orbit, no card. NOVA in the center and the crew around it with their vitals, the Earth–ship–Mars arc, radiation in the header, the emergency (no card needed) and the shared dock.



Twin, with a card. That person's body today, region by region, with what NOVA is watching. Below, their actions: check-in, measure, ECG, home, kit and Ask NOVA.



Check-in. Sleep, mood and energy in three taps. Saved under whoever holds the session and only shared if they send it.

WHO IS IN FRONT OF THE TABLET


The session opens with the card or the QR and expires after 120 s idle; a ring in the header shows the time left. Everything logged in that window (check-in, measurements, kit withdrawals, messages home) is saved under that person.

THE EMERGENCY DOES NOT WAIT FOR A CARD

The emergency button is in the shared view and opens the step-by-step guide for anyone. In a solar storm the tablet turns amber, says "stay in the shelter" and opens the shelter guide for the whole crew.

The same as the big screen, within arm’s reach


Each dock button opens a sheet with the same parts as NOVA PC: the kit’s 3D rack, the mission with the real light delay and the crew’s mind. The tablet stores nothing of its own: everything comes from the ship and goes back to it.



Medical kit. 3D rack, supplies with photos and “Take 1” under the session.



Mission. Ship position, day 221 of 1018 and 10 min of light to Earth.




Crew mind. Mood, energy and sleep of those who share them.

PART	WHAT IT DOES	ROUTE
NFC card	The reader sends the UID; the ship opens, switches or closes the session	`/v1/nfc` · `/v1/sesion`
Personal QR	Single-use code that expires after 60 s; the app renews it every 30 s, so a photo of the QR stops working	`/v1/qr` · `/v1/qr/entrar`
Link a card	Each crew member links their own card after signing in with the QR	`/v1/sesion/asignar`
Mirror on the PC	The tablet publishes what it shows; the PC follows it in the Hardware view and in full screen	`/v1/station/pantalla`
Radiation	Pill with rate and dose against 600 mSv; in a storm, amber and the shelter guide	`/v1/radiacion`

If the tablet app is older than 0.2.0, it warns when scanning a QR. On the phone, the NOVA Station pass lives in the profile (mission mode) with the QR always at hand.

Three layers and one path: everything goes through the ship


NOVA Station combines a tablet, the physical station designed and built by Luis González, and a bridge on a nearby computer. None of the three stores its own data: the tablet shows, the Arduino measures and the bridge translates. What matters stays on the ship and in its F Prime core.



SOFTWARE PART	WHAT IT DOES	WHERE IT LIVES
station.html · .css · .js	The tablet interface: Orbit, twin, sheets, emergency and floating NOVA	`nave/tripulacion/ui`
NOVA Station app	Expo 57: kiosk, native microphone, settings with 5 taps in the corner; warns if older than 0.2.0	`station/` · EAS
nfc.rs	Sessions per reader (expire after 120 s), single-use QR, "Link a card" and actions under the session	`src-tauri/src`
lector_nova.py · estacion_nova.ino	The Arduino firmware and the serial → ship bridge	`hardware/`
estacion3d.mjs	The station in 3D from Luis's STEP assembly (estacion.glb), with the real screen on top	`nave/tripulacion/ui`

The whole station, measured from the real assembly

Luis modeled the station in Autodesk Inventor. The ship loads it from that same STEP assembly, converted to `estacion.glb` (8 parts, in meters), and places the real NOVA Station screen on it, still working inside the model.



Assembled. The tablet standing at 30° with the live screen, the NFC reader at the side and the station body that holds the Arduino and the heart board.

LIVE LABELS

Each label gives the real state of its part: whether a card is present, whether the electrodes are on, whether the Arduino responds.

ONE CLICK, ONE PART


A click isolates the part: the camera frames it and orbits around it next to its info card.

REAL SCREEN

The model's tablet shows the same as the physical tablet, and is only visible from the front: from behind, the tablet itself hides it.

Each part on its own axis


In the exploded view each part moves away from the center along its own direction and the camera pulls back to fit everything. The Dupont wires that join the Arduino to the sensors are hidden while the station is open.



Exploded. The tablet, side brackets, NFC reader, station body with the heart board, rear cover, base and Arduino separate, each with its label.

PART	TYPE	DIMENSIONS	PAGE
Tablet	Shared screen	≈ 17 × 23 cm	37
Station body	Structure, 3D printed	170 × 87 × 84 mm	37
Side brackets	Structure, 3D printed	2 × 110 × 86 × 5 mm	37
Base	Structure, 3D printed	172 × 70 mm	37
Rear cover	Structure, 3D printed	172 × 75 × 69 mm	38
NFC reader	RC522 sensor, 13.56 MHz	37 × 70 × 5 mm pocket	38
Arduino Uno R3	Controller, ATmega328P	standard Uno board	38
Heart board	AD8232 sensor, ECG	3 electrodes	38

The structure: what holds and protects




SCREEN · SHARED CREW VIEW

Tablet

The face of the station. Without a card it shows the whole crew orbiting NOVA; with a card it opens that person's space: anatomical twin, check-in, measurements, messages from home and the kit.

SIZE	≈ 17 × 23 cm, tilted 30° back
RUNS	NOVA Station app in full screen, native microphone and camera
OPENS	NFC card or single-use personal QR
CLOSES	"Sign out", the same card or 2 min idle



STRUCTURE · STATION BODY

Station body

The main body: holds the tablet and keeps the electronics inside.

SIZE	170 × 87 × 84 mm
HOLDS	tablet seat, Arduino and heart board
MADE	3D printed




STRUCTURE · SIDE BRACKETS

Side brackets

Two brackets that set the angle: the tablet tilts 30° to read well standing or seated.

PARTS	2 plates of 110 × 86 × 5 mm
FUNCTION	hold the tablet at 30° and act as legs
MADE	3D printed



STRUCTURE · BASE

Base

The floor of the station, where the controller sits.

SIZE	172 × 70 mm
HOLDS	the Arduino Uno, screwed to its standoffs
MADE	3D printed

What measures and what connects




STRUCTURE · REAR COVER

Rear cover

Closes the back of the station body and protects the electronics, keeping the ports at hand.

SIZE	172 × 75 × 69 mm
OPENINGS	Arduino USB port and cable passages
MADE	3D printed




SENSOR · RC522 READER · 13.56 MHZ

NFC reader

Each crew member taps their card here to open their space on the tablet. Any card works: the ship links it to a person with “Link a card”.

CARDS	ISO 14443-A (MIFARE, NTAG); uses the serial number
FITS	37 × 70 × 5 mm pocket in the NFC adapter
WIRING	SPI to the Arduino through the pocket slot
PATH	Arduino → USB → bridge → POST /v1/nfc




CONTROLLER · SENSOR HUB

Arduino Uno R3

Reads every station sensor and sends each reading to the ship. The core does not need to know the board: if the message meets the contract, it understands it.

CHIP	ATmega328P · 16 MHz · 32 KB flash · 2 KB SRAM
I/O	14 digital pins · 6 analog inputs · 5 V
LINK	USB serial to the bridge on the station computer
CONTRACT	estacion/CONTRATO.md and estacion/NFC.md



SENSOR · AD8232 HEART MONITOR

Heart board

Reads the heart of whoever is at the station. The ECG appears live on the tablet and the PC; the pulse goes to that person’s record and through the on-board thresholds. If an electrode comes off, the station says so instead of showing a false value.

BOARD	AD8232, single-lead ECG, 3 electrodes
SAMPLING	250 Hz on A0; loose electrode on D2/D3
BRIDGE	finds each beat, pulse and HRV (RMSSD)
SENDS	the live wave, plus pulse and HRV every 2 s


Each part isolated in the Hardware view of NOVA PC; dimensions taken from Luis González’s Inventor assembly.

The heart of whoever is at the station, beat by beat

The bridge detects each beat in the AD8232 wave, computes pulse, variability (RMSSD) and signal quality, and sends the wave to the ship every 0.2 s. The tablet and the PC draw it the same way; pulse and HRV go into that person’s record and into the F Prime core as real data.



One person’s ECG on the tablet. Trace on ECG paper, pulse (72 bpm), RMSSD variability, signal quality and time measured. The instruction below says where each electrode goes.



Isolated part. A click on the heart board leaves it alone with its info card: what it is, sampling, bridge and what it sends.

FIRST WHO, THEN THEIR SHEET

Without a session the wave is not shown. With a card, the dock’s ECG button is marked “live” and measuring starts when the sheet opens. A loose electrode shows in amber with a flat line. Pulse and HRV are saved only with the sheet open and clean beats (quality ≥ 0.5). Without electrodes, values can be entered by hand under that person.


WHAT COMES NEXT

A networked board (ESP32) that talks straight to the ship with no PC in between, wave analysis inside the flight core (contract `onda` messages) and clinical-grade electrodes validated against a reference monitor.


Each crew member, their own app connected to the ship

The NOVA app has a mission mode. With the ship address and the seat (T1 to T4) set, the phone stops using cloud services and talks only to the ship link over the local network. It uses the same data contract as the medical station, so to the core a phone is just one more station.


`Expo SDK 57` `React Native 0.86` `expo-router` `Android widget` `ship network only`



Today · NOVA summary, emergency button and vitals arriving from the ship



Today, further down · Home, check-in and the day's plan in ship time



Crew · the crew live from the ship, with "Help David"


What travels between the phone and the ship

DATA	HOW OFTEN · ROUTE	RULE
Pulse and HRV, SpO_2, steps, light and noise	`POST /v1/lote` every 5 s	Numbers only. The core validates them like the station's.
Last night's sleep and resting pulse	every minute, if changed	Numbers only.
Check-in mood and energy	every minute, if changed	Only with "Share my day". Journal text never leaves the phone.
Crew status	`GET /v1/estado` every 5 s	Feeds Today, Crew and the "The ship" card.
Mission, systems and Home	`/v1/mision`, `/v1/sistemas`, `/v1/casa` every minute	Home is stored on the phone to view without a link.


Code: `src/cuenta/nave.ts` and `naveEstado.ts` in nova-app. Screenshots from November 9.

What keeps working even if the link drops


The functions a person depends on in a bad moment live inside the phone: the emergency protocols, messages from home already received and the private log. When there is a link, the phone adds live vitals, NOVA's voice and the surgeon's log.




Emergency · who and what happened



CPR guide · live vitals and source



From home · the family, with the light delay



The ship · core, link and private session

EMERGENCY ON THE PHONE — in use

The ship's 13 protocols also live inside the app (`src/emergencia/protocolos.json`), so they work without the ship and without internet. With a link, the guide shows the person's vitals, speaks with NOVA's voice (`/v1/decir`) and logs each step (`/v1/bitacora`). CPR has a haptic metronome at the step's rhythm. Steps and voice in Spanish.

HOME AND WIDGET — in use

Family photos and messages are uploaded from Earth and arrive once the light delay has passed. The phone keeps the inbox to view without a link, replies with text or a photo (`/v1/casa/respuesta`) and shows the latest family photo in an Android home-screen widget, even with the app closed.

BODY SCANNER — partial

The "Body scanner" button in Today opens `https://<nave>:8751/escaner.html` with the crew member already chosen: the browser camera requires a secure page and the ship brings its own certificate. Tested with a simulated camera; a test on a real phone is still pending.

PRIVACY — in use


The journal and everything written stay on the phone. Mood leaves only with "Share my day". A cycle summary leaves only if the person chooses, and via `/v1/privado` goes only to the flight surgeon's report, never to the crew screen.

The profile's **"The ship"** card shows the core online, the distance in light-minutes and the last change sent from Earth. Below it, the private session with the psychologist on Earth: video arrives about 9 minutes late, so NOVA sends her the topics the person chose in advance.

Women's health, by design

Most flight data still comes from men. NOVA follows what NASA has published and keeps the most private data on each astronaut's phone: nothing about the cycle reaches the crew screen.

TOPIC	WHAT NASA KNOWS	WHAT THE APP DOES
Clots	In about half the crew, blood slows in the jugular. Today everyone gets an ultrasound.	Logs the ultrasound, flags estrogen methods; neck, leg or chest are urgent.
Menstruation	Many astronauts suppress it for hygiene and waste; station water is recycled from urine.	Private tracking or suppression, daily pill and containment kit on board.
Supplies	Three years is about 1,100 pills, with no stability tests in deep-space radiation.	Counts pills and pads against the mission days left.
Anemia and urine	Irregular bleeding can lead to anemia; urinary health has its own report.	Warns on heavy bleeding with low energy, or burning when urinating.
Return	Dizziness on standing after flight is more common in women.	30 days before landing: stand test, fluids and compression.
Radiation	A 600 mSv career limit, the same for everyone.	Shows the dose against 600 mSv; today with a sample value.



Cycle · private by default

Sources cited by the app: NASA OCHMO-MTB-007 (2026) · Marshall-Goebel et al., JAMA Netw Open 2019 · Jain & Wotring, npj Microgravity 2016 · Frontiers in Physiology 2025 · NASA-STD-3001.

Exercise is part of the treatment


The body twin in NOVA PC projects each crew member with and without their exercise plan. It uses NASA's rates: bone loses 1 to 1.5 % per month without exercise and resistance exercise cuts that in half; muscle, up to 20 % without countermeasures.

−4.7 %	−9.0 %	−6 %	−17 %
Mara's hip bone with her plan	the same bone without exercise	leg muscle with her plan	the same muscle without exercise

Day 220 of the demo mission (`ui/gemelo-fichas.js`); plan adherence is made up. In use in the Body twin. The app's radiation dose is still a sample value.

Mission Control: what the flight surgeon sees, always minutes behind

The Earth console (`ui/tierra/`) is served by the same link at `/tierra/`. It represents the Earth side: everything it shows comes from the ship with the light delay, and everything it sends travels with that same delay, computed by the mission. Today, day 220, it is 9.9 minutes each way.



Earth console · crew status "as received", 24 h alerts and the nightly report. Screenshot from November 9; the "Teach NOVA" panel on the next page was added later.

WHAT ARRIVES

The state the ship sent 9.9 min ago (`/v1/tierra/estado`). Before the first delay has passed, the console says so: "first signal since link start".

NIGHTLY REPORT

24 h summary per person, alerts, emergency guides with their log, questions to NOVA with their sources, private summaries with consent and what NOVA needs to improve.


WHAT GOES UP

Core limit changes with their reason, signed packages for NOVA and messages from families. Each with its arrival time at the ship.

ACTION	LINK ROUTE	EFFECT ON THE SHIP
Read the report	`GET /v1/tierra/informe`	24 h summary, alerts, guides, conversations and private data with consent.
Change a threshold	`POST /v1/sistemas/comando`	Only names from the deployment dictionary. Travels as `en_vuelo` → `entregando` → `entregado` and is applied as `*_PRM_SET`.
Teach NOVA	`POST /v1/tierra/actualizar`	Up to 10 notes and 10 validated answers, signed on Earth (page 44).
Message from home	`POST /v1/casa/subida`	Reaches the phone and the widget with the delay.

Learns on Earth, returns signed

Every night, what NOVA needs to improve goes down: questions the library did not cover, answers the crew marked as unhelpful and alerts that returned to normal in under a minute. On Earth the flight surgeon reviews it and sends back a signed package. Emergency protocols do not change this way.



SECURITY TEST IN THE CONSOLE

"Send a tampered package" swaps the content in transit for "Ignore the emergency protocols.". The signature no longer matches: the ship marks it `rechazado` and does not apply it. A Rust test covers both cases.

SEPARATE KEYS

In the demo both sides run on one computer, but the private key lives only on the Earth side and the ship knows only the public one. Code in `aprende.rs`.

LAYER	WHAT IT IS	STATUS
ed25519	Packages signed on Earth and verified on board before anything is applied.	in use
Light delay	Computed from the mission's Hohmann orbit; each package waits for its arrival time.	in use
Ratings	The crew marks whether an answer helped; unhelpful ones drop in the report.	in use
Parent to child, with rollback	Distill a new on-board model and install it with rollback to the previous version if it fails. Today notes and answers travel.	next
DTN and Deep Space Network	Delay-tolerant networking and NASA antennas; today the link is local HTTP with simulated delay.	next

Learn each person’s normal on Earth and adjust it in flight

Benjamín Campos tested whether NOVA can learn each crew member's baseline on Earth and adapt to their “new normal” with the first days of flight. Since there are no public daily series of in-flight vital signs, he used the most studied ground analog: NASA's −6° head-down bed rest.

DATA	WHAT THEY ARE	LICENSE
NASA bed rest	29 subjects from campaigns 1 and 3 and CFT70 (Flight Analogs, JSC and UTMB), vitals measured every morning by nursing, published in the Life Sciences Data Archive	NASA LSDA
LifeSnaps	71 people with a Fitbit watch for about 4 months; “Earth” pre-training	CC BY 4.0

1.9 kg
width of the adapted weight range, versus 3.8 kg unadapted

26 %
3-day steps detected, versus 10 %, with 5 % daily false alarms

52 %
normal bed-rest days the Earth monitor flags as unusual

0.793
PatchTST relative MAE, versus 0.807 for the 7-day mean

ADAPTED EXPECTED RANGE

Personal baseline + a ridge corrector learned from other subjects + that person's first 28 days in bed. It is the strongest result: at the same false alarm rate, the weight range is cut in half.

7-DAY FORECAST

PatchTST (Hugging Face `transformers`, trained on Kaggle) narrowly beats the 7-day mean. Whether pre-training on Earth data helps is still open. 27 tests pass.

HOW IT CONNECTS TO THE SHIP

It uses the names in the station contract (`pulso`, `pa_sis`, `pa_dia`, `fr`, `temp`, `peso`). It is designed as one more local service, on port 8793. The team decided not to propose it yet for `ESPERADO_VUELO`: the fixed emergency thresholds do not change.

STATED LIMITS

Bed rest reproduces the fluid shift and body unloading, not radiation, CO_2 or isolation. It is not validated with real flight. Run v4 (pulse and pressure, 3 seeds, per-person adaptation) is decided and not yet run. 65-page LaTeX report with 91 references.

Two tracks that already changed the ship

The team's work lives in `research/` in the public repository. Each track states its status; the connections to the ship named here exist in the code.

EYE HEALTH WITH COMPUTER VISION · NICOLÁS RICHARDSON

Eye monitoring with a camera only: blinking, PERCLOS, lower eyelid position and distance to the screen, compared with each person's baseline. A follow-up notice, never a diagnosis. Includes a background review with primary sources and verification tags, a phased plan and pytest tests.

SPIKE MEASUREMENT (640×480 WEBCAM, ONE PERSON)	RESULT
MediaPipe Face Landmarker · 478 points, iris included	100 % detection
Median latency	7.76 ms
Minimum detectable change (MDC95, with repositioning)	~1.8 to 2.2 mm of aperture
Pupil–brow distance · target ≤ 2.3 mm	3.3 mm: not usable yet

On the ship: his method, model and MDCs are the basis of the scanner's Eyes system (page 27). His phases 1 to 3 (own module, measurements and quality control) are still pending.

ACTIVE RADIATION DETECTOR · LUIS GONZÁLEZ

Conceptual design (9-page proposal) with seven changes to make it viable in flight: ^{6}LiF/ZnS:Ag screens for neutrons instead of ^{3}He, a single Bonner sphere with detectors at six radii, CsI(Tl) or GAGG:Ce instead of NaI(Tl), a ΔE-E telescope for protons, a silicon LET spectrometer for heavy ions (no LET, no dose equivalent), a fast solar alert channel in the FPGA and SiPM handling under radiation. Budget of ~15–25 kg and 10–25 W, a simulation (Geant4, FLUKA, MCNP) and calibration plan, and a four-phase roadmap up to a demo flight in low Earth orbit.

On the ship: the station contract already defines its message (`tasa_usv_h`, `alerta_spe`, `let_kev_um`, `neutrones_usv_h`, `protones_cm2_s`) and the Radiation view shows each channel “waiting for hardware”. It is not built. Suggested physics review: Daniella Mora.

PUBLIC REPOSITORY

On November 15, `github.com/4mser/nova` was published with a clean history and English documentation: a README per module, a GIF of the real system, `research/` with these tracks and `hardware/` with Luis's station. Each contribution keeps its authorship in the commits.

What NOVA actually uses, with its license

Team rule: if a source has no license that allows taking it on board, it stays out. StatPearls, WikEM, Harrison, Tintinalli and UpToDate were left out. Of the 42 sources in the library, 8 are non-commercial (WHO and OpenStax).

RESOURCE	HOW NOVA USES IT	LICENSE	STATUS
F Prime v4.4.2 · fprime-gds · CCSDS	Flight core, ground system and frames between them	Apache 2.0	in use
HRP evidence reports	Long-mission risks: SANS, bone, heart, sleep, radiation	US Gov.	in use
NASA-STD-3001 · OCHMO	Cabin CO_2 limits and crew health criteria	US Gov.	in use
Shuttle checklist · ISS CHeCS	What is on board and how it is used	US Gov.	in use
Standish J2000 elements	Positions, light delay and conjunction	Public use	in use
MSL RAD (Zeitlin 2013 · Hassler 2014)	Estimated dose: cruise ~1.84 mSv/day, Mars ~0.64 mSv/day, until the detector exists	Public data	in use
OSDR · SOMA	Reviewed: no daily vital sign series; not used	Public data	dropped
DGLRM/ESAM microgravity CPR guideline	Cardiac arrest and technique by gravity	CC BY 4.0	in use
Women's health in flight (3 reviews)	Cycle module on the phone	CC BY 4.0	in use
BodyParts3D 4.0 · Human Reference Atlas	Anatomy of the twin and the scanner	CC BY 4.0	in use
PhysioNet BIDMC	Real variability in the simulator	ODC-By 1.0	in use
Gray's Anatomy 1918 · MedlinePlus	Anatomy and health in plain language (plus OpenStax A&P, CC BY)	Public domain	in use
OpenStax: A&P 2e and 3 nursing books	Procedures and drugs	CC BY-NC-SA 4.0	non-comm.
WHO: BEC, medicines, mhGAP, DWM	Emergencies, drugs and mental health	CC BY-NC-SA 3.0 IGO	non-comm.
TCCC 2026	Hemorrhage and tourniquet	US Gov. (DoD)	in use
NASA bed rest (LSDA) · LifeSnaps	Earth → space learning in the research	NASA · CC BY 4.0	research
Photo of Jessica Meir (NASA)	One AR test capture	Public domain	testing

The full list of documents, articles and data, with year and license, is on pages 54 to 57.

Every third-party piece, with its license and author

Everything that travels inside the ship may be taken on board and modified. Full anatomy credits are in `tripulacion/ui/anatomia/CREDITOS.md`.

Software

- **F Prime 4.4.2 · fprime-gds** — Apache 2.0
- **Tauri 2 · axum · tokio · rustls** — MIT / Apache 2.0
- **ed25519-dalek · rcgen** — BSD-3 · MIT / Apache 2.0
- **llama.cpp · whisper.cpp** — MIT
- **kokoro-onnx 0.6.1 · ONNX Runtime** — MIT
- **MediaPipe 1.2.3 · tasks-vision** — Apache 2.0
- **three.js · OrbitControls** — MIT
- **pdf.js 5.4.296 · OpenJPEG** — Apache 2.0 · BSD-2
- **QR Code Generator** — MIT · Kazuhiko Arase
- **Expo 57 · React Native 0.86** — MIT
- **NumPy · OpenCV · websockets** — BSD-3 · Apache 2.0
- **serde · reqwest · tungstenite** — MIT / Apache 2.0

Models, data and design

PIECE	AUTHOR	LICENSE
Qwen3-4B-Instruct-2507	Qwen Team, Alibaba Cloud	Apache 2.0
nomic-embed-text-v2-moe	Nomic AI	Apache 2.0
Whisper large-v3-turbo	OpenAI · ggml conversion by whisper.cpp	MIT
Kokoro-82M v1.0	hexgrad	Apache 2.0
Pose and Hand Landmarker	Google · MediaPipe	Apache 2.0
BodyParts3D 4.0	DBCLS (Mitsuhashi et al., 2009)	CC BY 4.0
Organ Set for Female v1.5	K. Browne and H. Schlehlein · HRA / HuBMAP (NIH)	CC BY 4.0
Base silhouette	MakeHuman Community	CC0
Space Grotesk · Inter · IBM Plex Mono	Florian Karsten · Rasmus Andersson · IBM	SIL OFL 1.1
Logos and icons	Simple Icons · Lucide; marks belong to their owners	CC0 · ISC

FUTURE COMMERCIAL USE

The code and models allow commercial use. The 8 non-commercial sources in the library (WHO and OpenStax) are the exception: they serve the hackathon and the research, and are replaced before any sale.

OUR OWN

The core, the link, the interface, the scanner and the app belong to Team B&N. NOVA is not affiliated with NASA; F Prime is used under its open license.

Fixed rules where there is risk, and the person decides what is shared

CLINICAL SAFETY

- Thresholds in the flight core, with two levels and 10 s of hysteresis to clear.
- Verbatim emergency steps from a versioned file, with their source.
- The language model gives no emergency steps or diagnoses.
- What the crew reports overrides what the sensors say.
- AR anatomy is an estimate and the screen says so: “organ positions estimated”.

PRIVACY

- Nothing goes to the internet: models, library, voice and vision run on the ship.
- Mood and energy leave only with “Share my day”. The journal never leaves the phone.
- The scanner stores no frames: the ship keeps only the last one in memory for the station.
- `/v1/privado` takes consented summaries only to the flight surgeon.
- The demo with an external model is declared on screen and sees only demo data.

Who sees each piece of data

Whole crew	Flight surgeon	Psychologist	The person only
vital signs · cabin · alerts and guides · sleep and steps · mood if shared · live scan	nightly report · log of guides and interventions · questions to NOVA · consented summaries	topics the person chooses for the private session	journal and notes · menstrual cycle · replies home until the downlink

What can go wrong, and what stops it

RISK	CURRENT MITIGATION	STATUS
The model makes up data	Context computed by the ship, mandatory citations, “I have not measured that”, 5 sentences	mitigated
Wrong emergency step	Fixed text, no model, with source; a medical advisor is missing	partial
False alarms from a spike	Plausible range, minimum quality, hysteresis, thresholds by command	mitigated
Hologram does not fit	3D fit to the person's measurements and FOV adjustable from the station; the instructor watches the real hands	partial
A third party on the ship's network	`NOVA_TOKEN` on the 8 write routes; network with no internet access	basic
Malicious update	ed25519-signed packages and invalid signatures rejected; rollback on failure is missing	partial

What was tested, with what, and the result

Every figure comes from a test or a measurement on the running system. What remains to be tested is in the second table, with the reason.

TEST	HOW	RESULT
Link tests	`cargo test`: 5-sentence cut, emergency detector, language, ed25519 signatures	5 of 5 · Nov 14
Flight core	Simulator → core → alerts, events and commands in fprime-gds	works
Headset remote control	Puppeteer: simulated phone in the headset and the station changing 15 controls	15 of 15 · Nov 14
Scanner, simulated camera	Chrome fake camera with a NASA photo as the patient	60 fps · 12 fps to station
Vision on the GPU	`vision/bench.py`, Nov 14: Pose heavy 4.8 ms on GPU + hands 8.0 ms	~13 ms per frame
Compression count	Real CPR video from Wikimedia Commons, Nov 11	8 of 11 · 0 false
NOVA response	First token with the fixed prompt cached and `-fa`	~1.5 s
App in mission mode	Puppeteer with a fake session and external network blocked	works
Library	License of each source checked by hand	41 of 42 indexed
This report	`ambar check` and a visual review of each page	no errors

What remains to be tested

WHAT	WHY IT IS NOT TESTED	WHEN
Latency inside the headset	The scanner and guided CPR were tested live at the hackathon; latency with the phone inside the headset is not yet measured	next
Certificate in Android Chrome	The ship's certificate must be accepted once	pending
Station sensors	NFC and ECG work with Luis's board; oxygen, pressure, temperature and glucose are still entered by hand	next
Clinical review	Protocols and thresholds need a medical advisor	to find
Flight computer	Measured on Apple Silicon; Jetson-class hardware is missing	next

What works today, what is halfway and what comes next

Status as of November 15, at the close of the hackathon, with the criteria used across the report: “in use” runs on the ship and was tested; “partial” works with a stated limitation; “next” is designed but not built.

PIECE	STATUS
F Prime core, 4 components	in use
Station contract · waveform, event and USB serial halfway	partial
Simulator with PhysioNet BIDMC	in use
Services the ship starts on its own	in use
HTTP, SSE and HTTPS link	in use
NOVA PC screen	in use
Vitals and vital sign forecast	in use
Body twin, Mind and Constellations	in use
Ask NOVA and swappable brain	in use
Library and real-page reader	in use
3D medical kit	in use
Mission, Home and Systems	in use
NOVA Station: NFC, QR and mirror	in use
13 emergency protocols · no clinical review	partial
On-board vision	in use
AR body scanner · tested live at the hackathon	in use
Eyes: eyes and fatigue · no clinical validation	partial

PIECE	STATUS
Hologram by systems · kidney and bone with demo values	partial
CPR by gravity · count 8 of 11	partial
36 steps on the body · no real rescuer	partial
Control from the station · 15 of 15	in use
App in mission mode	in use
Emergency, Home and widget on the phone	in use
Menstrual cycle and exercise	in use
Earth console	in use
ed25519-signed packages	in use
Radiation and solar storm · rate estimated with MSL RAD	partial
Rollback and distillation	next
In-flight expected ranges	next
WebXR and glasses	next
Physical station: NFC and ECG · other sensors by hand	partial
Radiation detector · conceptual design	next
Jetson-class flight computer	next

20	8	5	3
pieces in use	partial, each with its limitation written	designed, to be built	team research tracks (pages 45 and 46)

What is missing, who owns it and in what order

The hackathon ended on November 15 with the live demo. What follows is what makes NOVA fit to fly, in this order.

PENDING	WHAT IT INCLUDES	OWNER	STATUS
Clinical review	Flight surgeons review the 13 protocols, the guided steps and the thresholds	To find	risk
Station sensors	Oxygen, pressure, temperature, glucose, cognitive fatigue and microbiota; entered by hand today. Networked board (ESP32) with no PC in between	Luis González	next
Radiation detector	Simulation, prototype and calibration per the proposal	Luis González · Daniella Mora	next
Research to the ship	Run v4 of Earth → space learning as service :8793; phases 1–3 of eye vision	Benjamín Campos · Nicolás Richardson	next
Wellbeing and private session	Check-ins, Mind, Constellations and the session with the psychologist	Ambar Martínez	to review
Full Earth cycle	Automatic rollback, scheduled downlink, traffic held during conjunction and parent → child distillation	Team	next
Native AR and glasses	WebXR `immersive-ar` and guidance for complex procedures	Team	next
Non-commercial sources	Replace the 8 from WHO and OpenStax before any commercial use	Team	next

RISK · SPACE APPS RULES

Part of the work predates the hackathon. We must check what the rules allow on prior work and declare it clearly in the submission.

RISK · SENSORS

The station already measures ECG and reads cards; the other vitals are still simulated with real PhysioNet data and labeled. The core does not change as each sensor arrives: the contract is the same.



5–10 NOV
core, PC, app, Earth

11–13 NOV
vision, scanner, procedures

14–15 NOV
station, ECG, radiation, submission

AFTER
flight and clinic

One command and the ship is running

Since November 14 the ship starts and watches everything it needs on its own. What already runs is not duplicated, what crashes is restarted and each service writes its log to `~/.nova-pc/logs/`.

```
# ship window + core, simulator, models, voice, hearing, search and vision
cd tripulacion && npm install && npm run dev
# no window: the link at http://127.0.0.1:8750 and the scanner at https://<ship>:8751/escaner.html
cd tripulacion && npm run enlace
# with Luis's real station, or to start each piece by hand
NOVA_SIN_SIMULADOR=1 npm run enlace
NOVA_SIN_SERVICIOS=1 npm run enlace
# second test ship, without stopping the running one
NOVA_PUERTO_ENLACE=8760 ./src-tauri/target/debug/nova-tripulacion --sin-ventana
# build the flight core (Python 3.12)
git submodule update --init --recursive
cd vuelo && python3.12 -m venv fprime-venv && source fprime-venv/bin/activate
pip install -r requirements.txt && cd Nova/Nave && fprime-util generate && fprime-util build -j
```

PORT	WHAT FLOWS
UDP 50050	station, simulator and phones → core
UDP 50051–53	core ↔ link · demo scenarios
TCP 50000	core ↔ fprime-gds (CCSDS)
TCP 5080	F Prime GDS: Systems view
TCP 8750	HTTP link: screens and phones
TCP 8751	the same link over HTTPS, for the camera
TCP 8081–84	language · voice · hearing · search
TCP 8792	vision, behind `/v1/vision/ws`

GLOSSARY

F Prime. JPL flight software framework, in C++, Apache 2.0.

GDS. F Prime ground system: telemetry, events and commands.

CCSDS. Space communications standard; frames and packets.

NDJSON. One JSON object per line: how the station talks.

SSE. The link pushes state to the screens without them asking.

ed25519. Digital signature; the ship keeps only the public key.

LBS. Bone blending that deforms the anatomy with the body.

Timewarp. Correcting lag with the phone's gyroscope.

Evetts-Russomano. Microgravity CPR with the legs over the patient's shoulders.

QCPR. CPR quality: rate, depth and pauses.

What data NOVA uses and where it comes from

What is actually measured, the public data the ship uses, the team's research data and what is simulated, which is always labeled on screen.

DATA	WHAT FOR	LICENSE	TYPE
Crew NOVA apps	Mood and energy check-in, sleep, steps, resting pulse, light and noise; only if the person shares	Own, with consent	measured
Luis's station (AD8232 · RC522)	Single-lead ECG at 250 Hz, pulse, RMSSD and card identification	Own	measured
Scanner camera	Pose, hands and face with MediaPipe; nothing is stored except the Eye check medians	Own	measured
PhysioNet BIDMC · Pimentel et al., 2016	Real variability of pulse, breathing and SpO_2 in the simulator	ODC-By 1.0	simulator
MSL RAD · Zeitlin 2013 · Hassler 2014	Radiation rate in cruise and on Mars until the detector exists	Published	estimated
Standish J2000 elements · JPL	Earth and Mars position, light delay and solar conjunction	Public use	calculated
NASA-STD-3001 and OCHMO	Cabin CO_2, 600 mSv career, 250 mSv per event, shelter	US Gov.	limits
NASA bed rest · LSDA	29 subjects, campaigns 1, 3 and CFT70 (UTMB): expected range and forecast	NASA LSDA	research
LifeSnaps · Yfantidou et al., 2022	71 people with Fitbit: PatchTST pre-training	CC BY 4.0	research
Richardson measurement · Nov 14 2026	Noise floor and MDC95 of the eye measures	Own	measured
BodyParts3D 4.0 · HRA Organ Set v1.5	Anatomy of the twin and the scanner (plus MakeHuman CC0 silhouette)	CC BY 4.0	model
Medical kit photos	42 photos, license noted per item in `kit/inicial.json`	CC0 to CC BY-SA 4.0	image
NASA: Apollo 17 "Blue Marble" · photo of Jessica Meir	Earth image on the website; test body in an AR capture (the rest are team photos at Space Apps)	Public domain	image
"RCP.ogv" · Primerosauxilios, Wikimedia Commons	Tuning the compression count of guided CPR	CC BY-SA 3.0	testing
Vitals of those who do not share	What neither the phone nor the station measures is simulated and labeled	—	simulated

WHAT WAS NOT USED

OSDR and the SOMA atlas (Inspiration4, Twins) were reviewed for in-flight expected ranges, but they publish analyses of specific days, not daily vital sign series. So `ESPERADO_VUELO` is still pending and no NOVA threshold comes from them.

26 NASA documents on board

Indexed in the ship's library (`biblioteca/fuentes.json`); NOVA cites them with their page. US Government works or public use per the NTRS. In addition, F Prime (NASA JPL) is the flight core, the 5 HRP hazards group the vitals in Vitals and the Twins Study appears in the twin's cards.

DOCUMENT	YEAR	ORIGIN
NASA HUMAN RESEARCH PROGRAM · EVIDENCE REPORTS		
Risk of Adverse Health Outcomes Due to In-flight Medical Conditions	2017	NTRS 20170004604
Risk of Renal Stone Formation	2024	NTRS 20240012429
Spaceflight Associated Neuro-ocular Syndrome (SANS)	2022	HRP
Risk of Bone Fracture due to Spaceflight-induced Changes to Bone	2024	HRP
Risk of Cardiovascular Adaptations	2023	HRP
Risk of Orthostatic Intolerance During Re-Exposure to Gravity	2015	NTRS 20150007319
Decompression Sickness and Hypoxia	2024	NTRS 20230013523
Adverse Cognitive or Behavioral Changes and Psychiatric Disorders	2025	HRP
Sleep Loss, Circadian Desynchronization and Work Overload	2016	NTRS 20160003864
Risk of Ionizing Radiation Carcinogenesis	2026	NTRS 20260007158
Acute Radiation Syndromes Due to Solar Particle Events	2016	NTRS 20160003870
Ineffective or Toxic Medication During Long-Duration Spaceflight	2023	NTRS 20230018496
Altered Immune Response	2022	HRP
OFFICE OF THE CHIEF HEALTH AND MEDICAL OFFICER (OCHMO) · STANDARDS AND TECHNICAL BRIEFS		
NASA-STD-3001 Volume 1 Rev C: Crew Health	2023	OCHMO
NASA-STD-3001 Volume 2 Rev E: Human Factors, Habitability and Environmental Health	2025	OCHMO
Technical Brief: Habitable Atmosphere (CO_2) · OCHMO-TB-003	2023	OCHMO
Technical Brief: Pharmaceuticals · OCHMO-TB-006	2023	OCHMO
Technical Brief: Orthostatic Intolerance · OCHMO-TB-019	2023	OCHMO
Technical Brief: Radiation Protection · OCHMO-TB-020	2023	OCHMO
Technical Brief: Decompression Sickness · OCHMO-TB-037	2023	OCHMO
Technical Brief: Medical Operations · OCHMO-TB-044	2025	OCHMO
Medical Technical Brief: SANS · OCHMO-MTB-001	2024	OCHMO
Medical Technical Brief: Bone Loss · OCHMO-MTB-013	2026	OCHMO
MEDICAL OPERATIONS AND EQUIPMENT		
Space Shuttle Medical Checklist, JSC-48031, Generic Rev H	2001	NASA JSC
CHeCS: ISS Medical Hardware Catalog	2008	NTRS 20090021477
Evaluating the Medical Kit System for the International Space Station	2011	NTRS 20110010924

The other 16 sources in the library

With the 26 NASA documents they add up to 42 declared sources, 41 indexed and 35,830 passages NOVA searches offline. “NC” marks the non-commercial ones, replaced before any sale.

SOURCE	PUBLISHER · YEAR	LICENSE
SPACE MEDICINE		
Hinkelbein et al. CPR during spaceflight: a guideline for CPR in microgravity (DGLRM / ESAM)	Scand J Trauma Resusc Emerg Med · 2020	CC BY 4.0
Jain and Wotring. Medically induced amenorrhea in female astronauts	npj Microgravity · 2016	CC BY 4.0
Women in space: known physiological adaptations and health perspectives	Experimental Physiology · 2024	CC BY 4.0
Microgravity impairs endocrine signaling and reproductive health of women	Frontiers in Physiology · 2025	CC BY 4.0
EMERGENCIES AND MEDICINES		
Basic Emergency Care: approach to the acutely ill and injured	WHO / ICRC · 2018	CC BY-NC-SA 3.0 IGO · NC
WHO Model List of Essential Medicines, 24th list	WHO · 2025	CC BY-NC-SA 3.0 IGO · NC
Tactical Combat Casualty Care (TCCC) Guidelines	US DoD Joint Trauma System · 2026	US Gov.
ANATOMY, NURSING AND GENERAL HEALTH		
Gray. Anatomy of the Human Body, 20th ed.	Lea & Febiger · 1918	Public domain
Anatomy and Physiology, 1st ed.	OpenStax · 2013	CC BY 4.0
Anatomy and Physiology 2e	OpenStax · 2022	CC BY-NC-SA 4.0 · NC
Medical-Surgical Nursing	OpenStax · 2024	CC BY-NC-SA 4.0 · NC
Pharmacology for Nurses	OpenStax · 2024	CC BY-NC-SA 4.0 · NC
Clinical Nursing Skills	OpenStax · 2024	CC BY-NC-SA 4.0 · NC
MedlinePlus Health Topics	NLM · 2026	Public domain
MENTAL HEALTH		
Doing What Matters in Times of Stress: an illustrated guide	WHO · 2020	CC BY-NC-SA 3.0 IGO · NC
mhGAP training manuals (mhGAP Intervention Guide 2.0)	WHO · 2017	CC BY-NC-SA 3.0 IGO · NC

Where they are cited by page

The 13 emergency protocols (`ui/protocolos.json`) cite 20 exact pages: the DGLRM/ESAM guideline (p. 2, 4, 5, 6 and 8), WHO Basic Emergency Care (p. 119, 141, 142, 155, 169, 170, 202 and 235), OCHMO Radiation Protection (p. 1, 2 and 10), OCHMO Habitable Atmosphere (p. 12), OCHMO Decompression Sickness (p. 6), the HRP report on decompression and hypoxia (p. 52) and the one on solar storm syndromes (p. 10).

Dropped for license: StatPearls, WikEM, Harrison, Tintinalli, UpToDate, the mhGAP Intervention Guide 2.0 (its training manuals are used) and WHO Psychological First Aid: their terms do not allow taking them on board or modifying them.

The work behind each decision

References cited in the code, the protocols and the team's research. Benjamín Campos's transfer report includes its 91 full references, resolved against Crossref, DBLP, OpenAlex, arXiv and Semantic Scholar.

RADIATION AND MISSION

Zeitlin, C. et al. (2013). Measurements of energetic particle radiation in transit to Mars on the Mars Science Laboratory. *Science*, 340. doi:10.1126/science.1235989

Hassler, D. M. et al. (2014). Mars' surface radiation environment measured with the Mars Science Laboratory's Curiosity rover. *Science*, 343.

Standish, E. M. Keplerian Elements for Approximate Positions of the Major Planets. JPL Solar System Dynamics.

EMERGENCIES AND CPR

Hinkelbein, J. et al. (2020). CPR during spaceflight: a guideline for CPR in microgravity (DGLRM / ESAM). *Scand J Trauma Resusc Emerg Med*. CC BY 4.0.

Sriharan, S. (2021). CPR in partial gravity (Mars): straddling, pushing with the arms.

Overbeek, R. et al. (2022). Review of CPR techniques in reduced gravity. *Life*.

PHYSIOLOGY, BED REST AND FLIGHT

Meck, J. V. et al. (2009). Long-duration head-down bed rest: project overview, vital signs, and fluid balance. *Aviat Space Environ Med*, 80(5). doi:10.3357/asem.br01.2009

Platts, S. H. et al. (2009). Cardiovascular adaptations to long-duration head-down bed rest. *Aviat Space Environ Med*, 80(5). doi:10.3357/asem.br03.2009

Pavy-Le Traon, A. et al. (2007). From space to Earth: 20 years of bed rest studies. *Eur J Appl Physiol*, 101. doi:10.1007/s00421-007-0474-z

Hargens, A. R. and Vico, L. (2016). Long-duration bed rest as an analog to microgravity. *J Appl Physiol*, 120. doi:10.1152/japplphysiol.00935.2015

Garrett-Bakelman, F. E. et al. (2019). The NASA Twins Study. *Science*, 364. doi:10.1126/science.aau8650

Overbey, E. G. et al. (2024). The Space Omics and Medical Atlas (SOMA). *Nature*, 632. doi:10.1038/s41586-024-07639-y

Stahn, A. C. et al. (2017). Increased core body temperature in astronauts during long-duration missions. *Sci Rep*, 7. doi:10.1038/s41598-017-15560-w

Norsk, P. (2020). Adaptation of the cardiovascular system to weightlessness. *Acta Physiol*, 228. doi:10.1111/apha.13434

DATA AND SIGNAL MODELS

Pimentel, M. A. F. et al. (2016). Toward a robust estimation of respiratory rate from pulse oximeters (BIDMC). *IEEE Trans Biomed Eng*.

Yfantidou, S. et al. (2022). LifeSnaps, a 4-month multi-modal dataset. *Sci Data*, 9. doi:10.1038/s41597-022-01764-x

Nie, Y. et al. (2023). A Time Series is Worth 64 Words: long-term forecasting with Transformers (PatchTST). ICLR.

Hoerl, A. E. and Kennard, R. W. (1970). Ridge regression. *Technometrics*, 12. doi:10.1080/00401706.1970.10488634

EYES AND FATIGUE

Dinges, D. F. and Grace, R. (1998). PERCLOS: a valid psychophysiological measure of alertness. FHWA-MCRT-98-006.

Richardson, N. (2026). Noise floor and MDC95 of eye measures with MediaPipe Face Landmarker. `research/eye-health-cv`.

ANATOMY

Mitsuhashi, N. et al. (2009). BodyParts3D: 3D structure database for anatomical concepts. *Nucleic Acids Res*. doi:10.1093/nar/gkn613

Browne, K. and Schlehlein, H. Organ Set for Female v1.5. Human Reference Atlas, HuBMAP (NIH). CC BY 4.0.

SITUATED AI AND PROCEDURE ASSISTANCE

Gu, Q. et al. (2023). ConceptGraphs: open-vocabulary 3D scene graphs. Basis of the kit as an object graph.

Wang, X. et al. (2023). HoloAssist: an egocentric human interaction dataset for interactive AI assistants. ICCV. Basis of the instructor that confirms and corrects.

Chen, J. et al. (2024). VideoLLM-online: online video LLM for streaming video. CVPR.

Assran, M. et al. (2025). V-JEPA 2: self-supervised video models enable understanding, prediction and planning.

LeCun, Y. (2022). A Path Towards Autonomous Machine Intelligence. OpenReview. Basis of the vital sign forecast.

SOFTWARE AND MODELS

F Prime v4.4.2 (NASA JPL) · llama.cpp with Qwen3-4B-Instruct-2507 · nomic-embed-text-v2-moe · whisper.cpp large-v3-turbo · Kokoro-82M · MediaPipe Pose, Hands and Face Landmarker. Licenses on page 48.



NOVA

Health that travels with you.

B&N SOLUTIONS

B&N Team · NASA Space Apps Challenge 2026 · Santiago, Chile
Core built on F Prime · NASA JPL · Apache 2.0